



*Truck Mounted Log Loaders
Designed And Built In Canada!*



**Model
1028X**

Maximum rated lifting capacity
@ 10 foot radius: 28,000 lbs.

Boom Reach: 32 feet (Extend-A-Jib)

Cylinders Bore / Rod
Main Boom 7" X 3.5"
Jib Boom 6" X 3"
Stabilizers 6" X 3"

Normal Operating Pressure: 2,750 psi

Main Boom, Jib Boom and Cylinder Pins: 2.5" Diam.
"Super Impacto" case hardened to Rc50
(Tough core, hard surface)

Turntable Bearing: 39" Reservoir Capacity:
112 (US Gal.)

Hydraulic Pump Rated Flow & Pressure
@ 1200 RPM: 75 gallons per minute @ 3000 psi

Vanguard Cranes Inc.

20130B Stewart Crescent

Maple Ridge, B.C. Canada V2X 0T4

Phone: 604-465-1335 Fax: 604-465-0282

Email: sales@vanguardcranes.com

Web: www.vanguardcranes.com



*Truck Mounted Log Loaders
Designed And Built In Canada!*



Model
1028X

Available Options (* = recommended)	
Chelsea 440 PTO	* Chelsea 880 PTO
Aluminum Alberta Wide Load Clearance Lights	Aluminum Toolbox, Driver Side with Chainsaw Extension
Aluminum Toolbox, Passenger Side	Steel (Sloped Lid) Toolbox, installed behind Picker
Premier Pintle Hook on Tower	Operator Brush Guard
Swinglock Assembly (Single)	Swinglock Assembly (Dual)
* Front Bumper Reinforcement	Telescoping Stabilizer Arms c/w Hydraulic Cylinders & Controls
Float Valves installed on Swing and Main Boom	Single Rail Frame Insertion (if required)
* (1) twin electric fan oil cooler	(1) automatic electronic fan-control for cooler
Extra Lights on Boom (Qty 2)	Continuous Rotation Tower (Including Electric Swivel)
Chrome Cylinder Package	
Grapple Options	
38" 370 \circ Non Continuous Rotation	
44" 370 \circ Non Continuous Rotation	* 44" Continuous Rotation
1/3 Cord Pulp 370 \circ Non Continuous Rotation	44 " Twin Pin 370 \circ Non-Continuous Rotation
1/3 Cord Pulp Continuous Rotation	4 4 " Twin Pin Continuous Rotation

Vanguard Cranes Inc.

20130B Stewart Crescent

Maple Ridge, B.C. Canada V2X 0T4

Phone: 604-465-1335 Fax: 604-465-0282

Email: sales@vanguardcranes.com

Web: www.vanguardcranes.com